

Accessories of TNA TX7 Series Intelligent Panels

Model	Picture	Product	Function Description	Compatible
NC7004		Network & Communication Card	4-in-1 communication card, USB port, Ethernet Port, RS485/232 serial connection, CanBus network connection	TX7002 TX7004
LC7004		Loop Card	Dual loop card for TX7004-1/TX7004-2, capacity of 508 devices	TX7002 TX7004
NC7004-Modbus		ModBus Communication Card	ModBus card, 4-in-1 communication card, USB port, Ethernet Port, RS485/232 serial connection,	TX7002 TX7004
NC7004-IP		IP Network Card	TCP/IP Network card, 4-in-1 communication card, USB port, Ethernet Port, RS485/232 serial connection,	TX7002 TX7004
NC7008 NC7008-IP NC7008-Modbus		Network Card	NC7008 for CanBus Network Connection, NC7008-IP for TCP-IP Network, NC7008-Modbus for Modbus Protocol	TX7008 TX7008R
LC7008		Loop Card	Dual loop card for TX7008-6/ TX7008/TX7008R-6/TX7008R, capacity of 508 devices	TX7008 TX7008R
TX3251		IoT transfer module	Transfer TX7 panel and other brand panel information to IoT Cloud, RS232 and RS485 port available	TX7002 TX7004 TX7008 TX7008R
MC201		Fiber Optic Interface Module	Required NC7004 network card to configure to the TX7004 and TX7002 series	TX7002 TX7004 TX7008 TX7008R
TX7814		Dongle for TX7	USB Dongle access control of TX7 panel series	TX7002 TX7004 TX7008 TX7008R
TX7940		Printer	Thermo micro printer	TX7002

TX7812
Graphic Monitor Center
Software



Feature and Benefits

- Easy to use, direct and complete fire alarm graphic software
- Auto Display of all kinds of event such as Fire, Pre-alarm, Action, Supervisory, Disable and Fault in different color.
- Display the full device details, time of alarm and location and maintenance record folder.
- User privileges can be defined
- Support local panel remote control
- Support common toolbar for quick operation.

Technical Specification

Operating Software	Windows 7, 8 and Windows10
CPU	P4 1G or Higher
RAM	2G and above
HDD	8G and above
System Type	32 or 64 Bit OS

TX7932
Handheld Programmer



Feature and Benefits

- Write, read and erase device parameters
- Pluggable cable with end alligator clip to hold tight the terminals
- Low current consumption for longer battery lifespan
- Circuit protection against clip
- Auto power-off within 5 minutes

Technical Specification

Battery Required	2X1.5 AA / excluded
Current Consumption	Standby 0μA, In-use: 3mA
Material / Colour	ABS / Grey Glossy finishing
Dimension/LWH	130 x 54 x28 mm
Humidity	0 to 95% RH, Non condensing